

Steel DC Powered Scissor Cart 48 In. x 40 In. 1500 Lb. Capacity Blue / Yellow

MODEL CART-40-15-DC

Ergonomic Solutions / DC Powered and Manual Scissor Carts

PRODUCT OVERVIEW

The DC powered Scissor Cart table provides an unparalleled support in lifting, palletizing, loading, and unloading applications. The cart is raised or lowered with a DC powered motor. The unit rolls smoothly on two rigid and two swivel phenolic casters with brakes. The internal DC powered electric motor and battery is included on DC units. The built-in battery charger is AC powered and is included. Push buttons to raise and lower lift are located on a hand control with a coil cord, which is standard. The platform is equipped with perimeter pinch-point guard for OSHA compliance. The push handle is removable. Features an internal safety velocity fuse in each cylinder.

KEY FEATURES

- Solid steel constructions offers long lasting rugged use
- Push handle is removable for user convenience
- Phenolic casters with brakes make transportation easy
- Platform perimeter pinch-point guard is OSHA compliant

CORE PRODUCT DATA

ASSEMBLED WEIGHT
526 lbs

ASSEMBLED SIZE
36" W x 59" L x 42.5" H

SHIP WEIGHT
526 lbs

PACKAGE 1 SIZE
40" W x 64" D x 29" H

COLOR / FINISH
Blue / Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	1,500
Platform Width (in.)	40
Platform Length (in.)	48
Lowered Height (in.)	10-1/2
Raised Height (in.)	42-1/2
Lift Speed (sec.)	17
Caster Quantity/Diameter/Width (in.)	(4) 4 x 2
Caster Material	Phenolic
Caster Type	(2) Rigid (2) Swivel with Brakes
DC Motor Voltage	12
Battery Quantity	1
Electric Motor Watts	1600
AC Battery Charger Voltage	115
Battery Depth	11
Battery Width	7
Battery Height	9
Battery Weight	42
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA