

# Steel Floor Lock 5-5/8 to 6-1/4 In. Height Silver

**MODEL FL-LKL-5**

Facilities Maintenance / Polyurethane Floor Locks

## PRODUCT OVERVIEW

Floor locks are ideal for maintenance and construction facilities. The unit is designed to create a stable environment, while decreasing the chance of jostling or slight movement. The unit is constructed of steel with a thermoplastic polyurethane base. To use, place the unit close to a desired wheel or caster and raise until tension is built. Once secured, a simple locking device can be activated by applying pressure to the foot pedal.

## KEY FEATURES

- Steel construction for durability
- Thermoplastic polyurethane base for stability
- Locking device for quick service
- Lightweight for portability

## CORE PRODUCT DATA

|                                                                                                                                                 |                                                                 |                                      |
|-------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|--------------------------------------|
| <b>ASSEMBLED WEIGHT</b><br><b>2 lbs</b>                                                                                                         | <b>ASSEMBLED SIZE</b><br><b>3.875" W x 4.4375" L x 5.625" H</b> | <b>SHIP WEIGHT</b><br><b>2 lbs</b>   |
| <b>PACKAGE 1 SIZE</b><br><b>6" W x 5" D x 6" H</b>                                                                                              | <b>COLOR / FINISH</b><br><b>Silver</b>                          | <b>FREIGHT TYPE</b><br><b>Parcel</b> |
| <b>AVAILABILITY</b> Available<br>Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering. |                                                                 | <b>QUICKSHIP: YES</b>                |

PRODUCT SPECIFICATIONS

|                                          |                                  |
|------------------------------------------|----------------------------------|
| Lowered Height (in.)                     | 5-5/8                            |
| Raised Height (in.)                      | 6-1/4                            |
| Foot Pad Diameter (in.)                  | 2-9/16                           |
| Foot Pad Material                        | Thermoplastic polyurethane (TPU) |
| Mounting Plate (in.)                     | 3-7/8 x 3-9/16                   |
| Slotted Holes on Center (in.)            | 1-3/4 x 3-1/16                   |
| Mounting Plate Thickness (in.)           | 5/16                             |
| Slotted Mounting Hole Width/Height (in.) | 3/8 x 1/2                        |
| Inside Bolt Hole Spacing (in.)           | 2-13/16 X 1-3/4                  |
| Outside Bolt Hole Spacing (in.)          | 3-1/16 X 1-3/4                   |
| Suggested Caster Size (in.)              | 5                                |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1067>