

Steel Two Speed Commercial Direct Driver Blower 36 In. x 13-1/2 In. x 38 In. Black

MODEL MB-C-30

Facilities Maintenance / Commercial Direct Drive Blowers

PRODUCT OVERVIEW

The commercial direct drive swivel blower has a two speed, ball bearing motor that is permanently lubricated. The blower does not have a totally enclosed motor.

KEY FEATURES

- Enclosed wire front
- 3 blade design
- Meets OSHA standards and is UL listed
- Wheels included for quick movement



CORE PRODUCT DATA

ASSEMBLED WEIGHT
60 lbs**ASSEMBLED SIZE**
13.5" W x 36" L x 38" H**SHIP WEIGHT**
60 lbs**PACKAGE 1 SIZE**
34" W x 34" D x 11" H**COLOR / FINISH**
Black**FREIGHT TYPE**
Parcel**AVAILABILITY** Quote Required - Please Contact Sales**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Blade Diameter (in.)	30
Amps High	3.6
CFM High	6300
CFM Low	5500
Type	Swivel
Conductor Cord Length (in.)	72
Conductor Cord	SJT type 3
Motor Horsepower	1/3
Voltage/Phase	115V/1PH
OSHA	1910.212(a)(5)
UL Standards	507

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Louisville, KY 40232**

Warranty: **1 Year**

AVAILABLE PRODUCT RESOURCES

See the live product page for current documents and downloads.



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=125>