

# Steel Adjustable Double Mast Stacker 125 In. Raised Height 2200 Lb. Capacity Black / Yellow

**MODEL S-125-AA-DM**

Ergonomic Solutions / Double Mast Stackers with Powered Drive and Powered Lift



## PRODUCT OVERVIEW

Double mast fully powered electric stacker transports loads throughout warehouse facilities quickly and with less effort. High torque drive and lift motor handles heavy-duty jobs. Ergonomic handle features easy-to-operate throttle with infinite adjustment of forward and reverse speeds, lift/lower controls, proprietary safety-enhancing emergency reverse function, and horn. Includes an electromagnetic disc brake with automatic dead-man feature that activates when user releases the handle. Powered lifter has two lead acid deep cycle batteries, integral battery charger, and battery level gauge. Stacker rolls smoothly on poly-on-steel steer and load wheels. 3-4 hour operation at full charge - 8 hours when used intermittently.

## KEY FEATURES

- Emergency reverse belly switch instantly reverses direction
- Powered unit to minimize manual labor
- Diminishes amount of bending and twisting
- Simple movement controls

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**1190 lbs**

**ASSEMBLED SIZE**  
**50" W x 69" L x 82.5" H**

**SHIP WEIGHT**  
**1482 lbs**

**PACKAGE 1 SIZE**  
**60" W x 64" D x 77" H**

**COLOR / FINISH**  
**Yellow / Black**


**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

**QUICKSHIP: --**

## ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| Uniform Capacity at 0 - 62" (lb.)   | 2,200                                 |
| Uniform Capacity at 62 - 125" (lb.) | 1,500                                 |
| Service Range (in.)                 | 2-1/8 to 125                          |
| Fork Width/Length (in.)             | 4 x 42-1/8                            |
| Adjustable Fork Spacing (in.)       | 8-3/8 to 26-3/4 (OD)                  |
| Adjustable Leg Spacing (in.)        | 40 to 50 (ID)                         |
| Battery Depth                       | 11                                    |
| Battery Width                       | 14                                    |
| Battery Height                      | 9                                     |
| Battery Weight                      | 84                                    |
| Battery Freight Class               | 70                                    |
| Battery NMFC Number                 | 60680                                 |
| Battery NMFC Description            | UN2794 BATTERIES WET FILLED WITH ACID |
| Battery Subclass                    | 1                                     |
| Lithium Battery Configuration       | C -- Contained In                     |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA