

# Steel Economy Stabilizing Jack with Hard Rubber Wheels 18-1/4 In. x 16-5/8 In. x 41 In. 50,000 Lb. Static Capacity Yellow

**MODEL SJ-35-EF**

Loading Dock Equipment / Trailer Stabilizing Jacks



## PRODUCT OVERVIEW

Trailer stabilizing jacks are used to prevent up-ending of semi-trailers when they are not connected to a tractor during loading and unloading operations. Throughout the loading and unloading process it is always recommended to use two jacks, one on each side of the front of the trailer. The trailer must be situated on a flat, stable and improved (preferably concrete) surface, while the jack sits perpendicular to the underside of the trailer. Every jack is built of a high strength steel construction with a flush-type Zerk fitting for lubricating ACME screw. A yellow powder coat finish and a reflective collar for visibility at night are both included. Each jack meets OSHA regulations when used with wheel chocks. \*\*The color of handles included with...

## KEY FEATURES

- Square top plate
- Reflective collar increases visibility at night
- Manual raising and lowering mechanism
- Meets OSHA regulations when used with wheel chocks

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**57 lbs**

**ASSEMBLED SIZE**  
**16.625" W x 18.25" L x 41" H**

**SHIP WEIGHT**  
**57 lbs**

**PACKAGE 1 SIZE**  
**18" W x 42" D x 18" H**

**COLOR / FINISH**  
**Yellow**

**FREIGHT TYPE**  
**Parcel**

**AVAILABILITY**      Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

**QUICKSHIP: YES**

## ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                              |             |
|----------------------------------------------|-------------|
| Uniform Static Capacity (lb.)                | 50,000      |
| Uniform Lifting Capacity (lb.)               | 5,000       |
| Lowered Height (in.)                         | 41          |
| Raised Height (in.)                          | 57-1/2      |
| Wheel Size (in.)                             | 8           |
| Wheel Type                                   | Hard Rubber |
| Base Type                                    | Economical  |
| Handles (qty.)                               | 4           |
| Top Plate Width/Length (in.)                 | 5 x 5       |
| Swivel Head Maximum Extension Distance (in.) | 7-5/16      |
| Swivel Head Screw Diameter (in.)             | 1-1/2       |
| ACME Threads OD (in.)                        | 1-1/2       |
| ACME Threads Per Inch                        | 8           |
| Overall Width (in.)                          | 16-5/8      |
| Overall Depth (in.)                          | 18-1/4      |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA