

Steel Narrow Mast Stacker DC Powered 62 In. Raised Height Fixed Fork 27 In. Fork Width 1,500 Lb. Capacity Black / Yellow

MODEL SNM15-62-FF-27

Ergonomic Solutions / Narrow Mast Stackers with Powered Drive and Powered Lift



PRODUCT OVERVIEW

The narrow mast stacker is great for the shipping and manufacturing facilities. The stacker provides a fast efficient solution to loading and unloading products in closely confined areas. The stacker features a simple throttle design for lifting control, as well as, infinite forward and reverse speed adjustments. The unit drives on poly on steel steering and load wheels, which provide excellent maneuverability. A battery charger, gauge and horn are included. Models are available with fixed or adjustable forks as well as fixed or adjustable leg supports.

KEY FEATURES

- Emergency reverse belly switch instantly reverses direction
- Stacker is an efficient solution to loading and unloading in closely confined areas
- Throttle design lifts and controls speed adjustments for ideal operation and optimal results
- Includes poly-on-steel wheels for excellent maneuverability and fixed forks for maximum efficiency

CORE PRODUCT DATA

ASSEMBLED WEIGHT
768 lbs
ASSEMBLED SIZE
28" W x 66" L x 77.25" H
SHIP WEIGHT
772 lbs
PACKAGE 1 SIZE
60" W x 75" D x 84" H
COLOR / FINISH
Black / Yellow
FREIGHT TYPE
LTL Palletized
AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: YES

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	1,500
Service Range (in.)	2 to 62
Fork Width/Length (in.)	5-9/10 x 42-1/8
Fixed Fork Spacing (in.)	26-3/4
Overall Mast Height (in.)	78
Drive Motor	DC 24V / 0.4 KW
Lift Motor	DC 24V / 2.0 KW
Battery	(2) 12V / 80 Ah
Battery Charger	24V / 8 amp
Operation Time with Constant Use (hrs.)	3 to 4
Operation Time with Intermittent Use (hrs.)	8
Turning Radius (in.)	88-5/8
Travel Speed - Loaded (MPH)	1.24
Travel Speed - Unloaded (MPH)	1.86
Battery Depth	8
Battery Width	14
Battery Height	7
Battery Weight	56
Battery Freight Class	60
Battery NMFC Number	60700
Battery NMFC Description	Gel batteries on unit
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA