

# PVC Vinyl Strip Door Material 200 Feet Roll Clear

**MODEL TG-1200-ROLL**

Loading Dock Equipment / Vinyl Strip Doors



## PRODUCT OVERVIEW

Roll vinyl strip door material for replacing damaged strips or adding new strips.

## KEY FEATURES

- Vinyl strip design helps to minimize heating and cooling costs
- Clear strips offer visual clarity & employee safety
- Fire resistant vinyl construction is self-extinguishing
- Smooth surface design allows user to comfortably enter & exit

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**128 lbs**

**ASSEMBLED SIZE**  
**12" W x 0.12" L x 2400" H**

**SHIP WEIGHT**  
**164 lbs**

**PACKAGE 1 SIZE**  
**30" W x 36" D x 18" H**

**COLOR / FINISH**  
**Clear**


**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY** Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

**QUICKSHIP: YES**

## ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                                             |            |
|-------------------------------------------------------------|------------|
| Roll Length (ft.)                                           | 200        |
| Tensile Strength (PSI)                                      | 2635       |
| Maximum Tensile Elongation (percent)                        | 388        |
| Graves Tear Load (lb.)                                      | 35.4       |
| Graves Tear Extension (in.)                                 | 2.07       |
| Load at 100% Elongation (lbs.)                              | 32.2       |
| Strength at 100% Elongation (PSI)                           | 1181       |
| Stiffness in Flexure - 23 degrees Celsius (PSI)             | 1805       |
| Brittleness Temperature by Impact (degrees Celsius)         | 35         |
| Recommended Operating Temperature - Range (degrees Celsius) | -10 to 140 |
| Specific Gravity                                            | 1.22       |
| Haze Transmittance (percent)                                | 6.30       |
| Luminous Transmittance (percent)                            | 82.80      |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA