

PVC Vinyl Strip Door 2/25 In. Roll 2/25 In. Thickness 8 In. x 3600 In. Clear

MODEL TG-800-ROLL

Loading Dock Equipment / Vinyl Strip Doors



PRODUCT OVERVIEW

Roll vinyl strip door material for replacing damaged strips or adding new strips.

KEY FEATURES

- Vinyl strip design helps to minimize heating and cooling costs
- Clear strips offer visual clarity & employee safety
- Fire resistant vinyl construction is self-extinguishing
- Smooth surface design allows user to comfortably enter & exit

CORE PRODUCT DATA

ASSEMBLED WEIGHT
107 lbs

ASSEMBLED SIZE
8" W x 0.08" L x 3600" H

SHIP WEIGHT
107 lbs

PACKAGE 1 SIZE
24" W x 24" D x 14" H

COLOR / FINISH
Clear


FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: YES

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Length (ft)	300
Package Contents	(1) 300 Ft Roll PVC Vinyl Strip Door Material
Tensile Strength (PSI)	2635
Maximum Tensile Elongation (percent)	388
Graves Tear Load (lb.)	35.4
Graves Tear Extension (in.)	2.07
Load at 100% Elongation (lbs.)	32.2
Strength at 100% Elongation (PSI)	1181
Stiffness in Flexure - 23 degrees Celsius (PSI)	1805
Brittleness Temperature by Impact (degrees Celsius)	35
Recommended Operating Temperature - Range (degrees Celsius)	-10 to 140
Specific Gravity	1.22
Haze Transmittance (percent)	6.30
Luminous Transmittance (percent)	82.80

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA